



## FELT WAX RING

Material Safety Data Sheet

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Manufacturing Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheet.

SECTION I - GENERAL INFORMATION	
Black Swan Manufacturing Co. 4540 W. Thomas Street Chicago, IL 60651-3318 Telephone No: 1-773-227-3700 Fax No: 1-773-227-3705	For chemical emergencies during transportation only call  INFOTRAC <b>1-800-535-5053</b> 24 hours per day - 7 days a week
<b>Date Prepared</b> 01/01/08	<b>Trade Name</b> FELT WAX RING
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION	
HAZARDOUS COMPONENTS	CAS#      APPROX%    ACGIH-TLV    OSHA-PEL
THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS ACCORDING WITH OSHA 1910.1200.	
*Title III Section 313 Supplier Notification: this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency planning and community Right-to-Know Act of 1966 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.	
SHIPPING INFORMATION	SPECIAL HAZARD DESIGNATIONS
	<u>HMIS</u> <u>NFPA</u> <u>HAZARD</u>

NOT HAZARDOUS FOR SHIPPING PURPOSES.	HEALTH 0 0 FLAMMA-BILITY 1 1 REACTIVITY 0 0 PROTECTIVE EQUIPMENT X X	<u>RATING</u> 0 - MINIMAL 1- SLIGHT 2- MODERATE 3- SERIOUS 4- SEVERE
SECTION III - PHYSICAL DATA		
<b>APPEARANCE</b> SOLID AMBER	<b>ODOR</b> NEARLY ODORLESS	<b>BOILING POINT</b> N/A
<b>SPECIFIC GRAVITY (H2O=1)</b> .85	<b>VAPOR PRESSURE (mm Hg.)</b> NIL	<b>VOLATILE BY VOLUME (%)</b> NIL
<b>VAPOR DENSITY (AIR=1)</b> 10+	<b>EVAPORATION RATE (BUAC=1)</b> N/A	<b>SOLUBILITY IN WATER</b> NIL
SECTION IV - FIRE AND EXPLOSION HAZARD DATA		
<b>FLASH POINT ( METHOD USED)</b>	<b>FLAMMABLE LIMITS</b>	<b>LEL UEL</b>
500°F MIN P.M.	(PERCENT BY VOLUME)	ND ND
<b>FIRE EXTINGUISHING MEDIA</b> CARBON DIOXIDE, FOAM, DRY CHEMICAL		
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> DO NOT USE WATER AS IT MAY BE INEFFECTIVE IN EXTINGUISHING A FIRE INVOLVING THIS MATERIAL.		
<b>UNUSUAL FIRE AND EXPLOSION HAZARD</b> NONE		
SECTION V - HEALTH HAZARD DATA		
<b>PRIMARY ROUTES OR ENTRY</b> __Inhalation __X__Skin contact ____Eye contact ____Ingestion		

**EFFECT OF OVEREXPOSURE**

MOST IRRITATE SKIN.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

SKIN DISORDERS.

**EMERGENCY AND FIRST AID PROCEDURES**

SWALLOWING: NONE NECESSARY

SKIN CONTACT: NONE NECESSARY AS A SOLID. CONTACT WITH MELTED PETROLATUM CAN CAUSE THERMAL BURNS, FLUSH WITH WATER TO COOL AFFECTED AREAS AND CONTACT A PHYSICIAN IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN.

EYES: FLUSH WITH WATER, CALL A PHYSICIAN.

**SECTION VI - REACTIVITY**

STABILITY	UNSTABLE		<b>CONDITIONS TO AVOID</b>
	STABLE	X	EXCESS HEAT, DIRECT FLAME.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

STRONG OXIDIZERS.

**HAZARDOUS DECOMPOSITION PRODUCTS**

COMBUSTION WILL PRODUCE CARBON MONOXIDE AND OTHER ASPHYXIANTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		<b>CONDITIONS TO AVOID</b>
	WILL NOT OCCUR	X	NONE KNOWN

**SECTION VII - SPILL OR LEAK PROCEDURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

RECOVER FREE SOLID. IF MOLTEN PARAFFIN SPILLED, SOLIDIFY AND RECOVER.

**WASTE DISPOSAL METHOD**

INCINERATE PER LOCAL, STATE AND FEDERAL REGULATIONS.

**SECTION VIII - SPECIAL PROTECTION INFORMATION**

<b>RESPIRATORY PROTECTION (Specify type)</b> N/A	
<b>VENTILATION</b> N/A	
<b>PROTECTIVE GLOVES</b> N/A	<b>EYE PROTECTION</b> N/A
<b>OTHER PROTECTIVE EQUIPMENT AND HYGIENIC PRACTICES</b> N/A	
SECTION IX - SPECIAL PRECAUTIONS	
<b>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING</b> AVOID EXCESSIVE HEAT OR DIRECT FLAME.	
<b>OTHER PRECAUTIONS</b> WHEN DEALING WITH HOT MELTED PETROLATUM, SPECIAL PRECAUTIONS PERTINENT TO YOUR OPERATION SHOULD BE AS FOLLOWED. AS WITH ANY PETROLEUM HYDROCARBON, PERSONAL HYGIENE IS IMPORTANT TO ASSURE THAT PROLONGED OR REPEATED CONTACT IS MINIMIZED. HANDS AND OTHER EXPOSED AREAS SHOULD BE WASHED THOROUGHLY WITH SOAP AND WATER AFTER CONTACT, ESPECIALLY BEFORE EATING AND/OR SMOKING.	
This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.	

---

**Black Swan Mfg. Co.** Telephone:773-227-3700 E-mail: [info@blackswanmfg.com](mailto:info@blackswanmfg.com)  
4540 W. Thomas Street Wats:800-252-5796 Web site:<http://www.blackswanmfg.com>  
Chicago, IL 60651-3318 Fax:773-227-3705