



SECTION 1 - IDENTIFICATION

Table with 2 columns: Manufacturer information (Black Swan Mfg. Co., 4540 W. Thomas St., Chicago, IL 60651-3318, Tel.: 800-252-5796, Fax: 773-227-3705, Web Site: www.blackswanmfg.com, E-mail: info@blackswanmfg.com) and For any Transportation or Medical Chemical Emergencies call: INFOTRAC (800) 535-5053 OR (352) 323-3500, 24 hours per day - 7 days a week. Product Name: Plumbers Grease. Recommended Use: Lubricates stems of faucets, valves, ball cocks, etc.

SECTION 2 - HAZARD(S) IDENTIFICATION

Table with 4 columns: Labels (None), Signal Word (None), HMIS (HEALTH 1, FLAMMABILITY 1, REACTIVITY 0), NFPA (HEALTH HAZARD 1, FIRE HAZARD 1, REACTIVITY 0), GHS Classification (Health: Acute Toxicity: Not Established, Skin Irritation: Not Established, Eye Irritation: Cat 2A, Skin Sensitization: NO; Environmental: Acute Aquatic Toxicity: Not Established, Chronic Aquatic Toxicity: Not Established; Physical: None), Hazardous Statements (H320: Causes eye irritation), and Precautionary Statements (P102: Keep out of reach of children, P262: Do not get in eyes, P264: Wash thoroughly after handling, P270: Do not eat, drink or smoke when using this product).

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Table with 5 columns: Chemicals, CAS#, EINECS#, REACH Pre-registration Number, and Approx %. Rows include Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS# 64742-65-0, N/A, N/A, 40-60%) and Distillates (petroleum), solvent-refined heavy naphthenic (CAS# 64741-96-4, N/A, N/A, 30-50%).

SECTION 4 - FIRST-AID MEASURES

Inhalation: Remove into fresh air. If not breathing, give artificial respiration. Call a physician. Skin: Rinse skin with water for at least 15 minutes. Take off contaminated clothing/shoes and wash before reuse. Get immediate medical attention. Eyes: Flush eyes with large amounts of water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do so. Get immediate medical attention. Ingestion: If swallowed rinse mouth. DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5 - FIRE-FIGHTING MEASURES

Fire Hazard: Directly spraying extinguishing media onto hot burning products may cause frothing and spreading of fire. Combustion Products: None. Extinguishing Media: Use an extinguishing agent suitable for the surrounding fire. Unsuitable Extinguishing Media: None known. Protective Equipment: Self-contained breathing apparatus {(SCBA), MSHA/NIOSH} and protective clothing. Special Fire Fighting Procedures: Evacuate enclosed areas, stay upwind. Closed or confined quarters require self-contained breathing apparatus, positive pressure hose masks or airline masks. Use water spray to cool containers, to flush spills from sources of ignition and to disperse vapors.

## GHS SAFETY DATA SHEET

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Minimize skin contact. Provide adequate ventilation.  
**Protective Equipment:** None.  
**Emergency Procedures:** None.  
**Environmental Precautions:** Avoid runoff into storm sewers, ditches and waterways.  
**Methods for Cleaning Up:** Vacuum dust with equipment fitted with HEPA filter and place in a closed waste container. Add sand, earth, or other absorbent to spill. Prevent entry into sewers, water courses, basements and confined areas.

### SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep containers closed when not in use.	Store in a dry, well ventilated place. Keep cool. Keep container tightly closed. <b>Incompatible Materials:</b> Strong oxidants such as Chlorine Gas.

### SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>Exposure Limits</u>	<u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<u>ACGIH-TLV</u> TWA: 5mg/m <sup>3</sup>	10mg/m <sup>3</sup>	TWA: 5mg/m <sup>3</sup>
Distillates (petroleum), solvent-refined heavy naphthenic	TWA: 5mg/m <sup>3</sup>	10mg/m <sup>3</sup>	TWA: 5mg/m <sup>3</sup>

**Engineering Controls:** Sufficient ventilation in order to control worker exposure to airborne contaminants.  
**Ventilation:** Local ventilation is adequate.  
**Personal Protective Equipment – Respiratory:** Use a properly fitted particulate filter respirator. **Skin:** Oil resistant gloves. Chemical resistant apron. **Eyes:** Splash goggles/Face shield.

### SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

<b>Appearance:</b> Amber	<b>Flash Point:</b> 380°F	<b>Vapor Pressure:</b> 0.01
<b>Odor:</b> Petroleum	<b>Specific Gravity:</b> 0.90	<b>Flammability:</b> Not Established
<b>pH:</b> Not Established	<b>Solubility (H<sub>2</sub>O):</b> Very slight at room temperature	<b>Flammability Limits:</b> LEL – 1%
<b>Melting Point:</b> Not Established	<b>Evaporation Rate:</b> <0.01	UEL – 7%
<b>Freezing Point:</b> Not Established	<b>Vapor Density:</b> 5	
<b>Boiling Point:</b> 500°F	<b>VOC:</b> 0 g/l	

### SECTION 10 – STABILITY AND REACTIVITY

**Stability:** Stable.  
**Hazardous polymerization:** Will not occur.  
**Conditions to avoid:** None.  
**Incompatible materials:** Strong oxidants such as Chlorine Gas.  
**Hazardous decomposition products:** Fumes, Smoke, CO<sub>x</sub>, SO<sub>x</sub>, NO<sub>x</sub>, when combusted.

### SECTION 11 – TOXICOLOGICAL INFORMATION

<u>Hazardous Chemicals</u>	<u>Toxicity</u>	<u>LC<sub>50</sub></u>
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<u>LD<sub>50</sub></u> Dermal: >5000 mg/kg (rabbit)	N/A
	Oral: >5000 mg/m <sup>3</sup> (rat)	
Distillates (petroleum), solvent-refined heavy naphthenic	Dermal: >5000 mg/kg (rabbit)	N/A
	Oral: >5000 mg/kg (rabbit)	

**Likely Routes of Exposure:** Inhalation, Skin Contact and Eye contact.  
**Symptoms and Effect – Inhalation:** Respiratory tract irritation. **Skin Contact:** Reddening and irritation. **Eye Contact:** May cause mild irritation.  
**Ingestion:** None.  
**Long-Term Effect:** Product has a low order of acute, oral, and dermal toxicity. Product containing the eyes may cause irritation. Repeated skin contact may cause skin irritation or dermatitis because these types of products tend to remove natural emollients from the skin.  
**Pre-Existing Conditions:** Pre-existing dermatitis or skin disease.

# GHS SAFETY DATA SHEET

## SECTION 12 – ECOLOGICAL INFORMATION

**Ecotoxicity:** None known.

**Persistence & Degradability:** None known.

**Bioaccumulative Potential:** None known.

**Mobility in soil:** In normal use, emission of Volatile Organic Compounds (VOC's) to the air takes place, typically at a rate of 0 g/l.

## SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

## SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated.

## SECTION 15 – REGULATORY INFORMATION

**Precautionary Label Information:** None.

**Risk Phrases:** None.

**Safety Phrases:** S2-Keep out of reach of children.

## SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets. **DATE: 01/01/2021**